

Manufacturer	Source colour	Light Output Area/Length	Injection process	Input voltage
PHLOX	LEDW	BL 150x40	SLLUB	Q - 1R - 24V
	Source type	Product type	Range	Number of light sources' rows per cicu


PHLOX® EXCLUSIVE LIGHT PROCESS  
WORLDWIDE PATENT ISSUED

**NEW!**

# SLLUB (Super Long life Ultra Bright) White led Backlight 150x40

LESS THAN 20% LUMINANCE LOSS AFTER 100 000 HOURS (\*)  
LESS THAN 10% CHROMATICITY SHIFT AFTER 100 000 HOURS (\*)


PHLOX - LEDW - BL - 150x40 - SLLUB - Q - 1R - 24V



## Illumination

Luminance minimum	<b>≥40 000 cd/m<sup>2</sup> continuous mode</b>
Uniformity minimum	<b>≥90% (+/- 10%)</b>
Source Type	White LED
Colour Temperature	5700°K (+/-500)
Light Angular Distribution	30° 1/2 angle
Expected Life	<b>&gt; 100 000 hours</b>

## Electrical

Input Voltage	24 VDC (continuous mode)
Input Current	≤700 mA (continuous mode)
Cable length	2 M - Ø 2.7 mm (6.56 ft - Ø 0.10")
Connector	None
Cable pinout	
CE Conformity	Yes
Strobe mode	Max. Cur: 2.8A / Pulse Width: 10ms / Duty Ratio: 1/10


## Outer unit

L x W x H	193 x 77 x 8.5 mm (3.54 x 3.35 x 0.334")
Housing Material	Black Anodized Aluminium
Weight	240 g (8.47 oz)
Mounting	4 bore holes (D8 for the first 3.5 mm of height, D4 for the other 5.5 mm)

## Environmental

Max. Operating Humidity	95% non-condensing
Operating Temperature	50°C (122°F) max
Storage Temperature	60°C (140°F) max
Shelf life	12 months from date of purchase
Max.temp.on housing	+80°C (+176°F)

area of temperature measurement  
30mm all along the edges of the back of  
the black anodized aluminium housing  
(see image)



Do not cover the backlight when it's switched on.

## Accessories

**LED Dimmer:** 28V-5A very compact and easy to use  
Product key: PHLOX DIM LIGHT

**Power supply:** 110V and 220V  
Product key: ALIM-24V-2.5A60WEU or ALIM-24V-2.5A60WUS

**LED Strober:** 28V - 5A (up to 40A in pulse mode)  
Pulse width between 2µs and 10ms  
Product key: PHLOX STROBE LIGHT



CLASS 0: NO RISK (CIE S2009:2002/NF EN 62471)

**RoHS** directive compliant

Each PHLOX Backlight is provided with:

- 24 months warranty
- Certificate of uniformity and luminance
- Seal of quality on the back

May 19, 2018

**SLLUB Backlights by PHLOX®** offer the **best life cycle**, the **best chromaticity stability** and the **best luminance on the market**, all in an ultra compact and IP-65 body. **PHLOX®** is the only manufacturer to provide uniformity and luminance datas on the quality control seal positioned at the back of every backlight.


## DESIGNED

### FOR YOUR APPLICATION

Bottle inspection (glass and plastic)  
Particle measurement  
Picture digitalization  
Dimensional control  
Shaping control  
Quality control with transparency.

## & YOUR INDUSTRIAL SECTOR

Glassmaking  
Pharmaceutical/Cosmetics  
Automotive  
Agribusiness  
Electronics  
Aeronautics and space.



PROPRIÉTÉ DE PHLOX SA- REPRODUCTION INTERDITE SAUF ACCORD ÉCRIT	
PHLOX-LEDW-BL-150X40-SLLUB-Q-1R-24V	
TEL: 04 42 90 76 20 FAX: 04 42 90 76 21	